Declaration of Perfomance

Nr. 01260000-PYRO-SAFE-DG

PYRO-SAFE DG

Date: 25.09.2018
Rev. 04

Unique identification code of the product type
PYRO-SAFE DG, PYRO-SAFE DG-SC,
PYRO-SAFE DG-CR, PYRO-SAFE DG-CR BS, PYRO-SAFE DG-CR SK,
PYRO-SAFE DG-CRF

Intended use:
Intumescent products for fire sealing and fire stopping purposes without a defined final use (IU1)

Producer
svt Brandschutz Vertriebsgesellschaft mbH International
Gluesinger Strasse 86
D - 21217 Seevetal

System for assessing and verifying constancy of performance
System 1

European Assessment Document
EAD 350005-00-1104

European Technical Assessment
ETA-16/0268

EC cerificate of conformity
0761-CPR-0558

Technical Assessment Body
Deutsches Institut für Bautechnik (DIBt), Berlin

The notified body
Materialprüfanstalt für das Bauwesen Braunschweig, code number 0761

Declared performance

Essential characteristics	Performance	Harmonised technical specification
Reaction to fire		
PYRO-SAFE DG (For layers of a thickness ≥ 1 mm to ≤ 2 mm on metal substrates (melting point ≥ 1.000 °C) and on classified substrates of class A1)	B-s1,d0	DIN EN 13501-1
PYRO-SAFE DG-CR (Nominal thickness 0,6 mm to 2,2 mm free standing, on mineral substrates (density ≥ 800 kg/m³) and on classified substrates of class A1)	C-s1,d0	
PYRO-SAFE DG-CR BS, PYRO-SAFE DG-SC, PYRO-SAFE DG-CR SK, PYRO-SAFE DG-CRF	E	
Emission of dangerous substances	no dangerous substances	ETA 16/0268
Use category	Type X, Y_1, Y_2, Z_1, Z_2	EOTA TR 024

The performance of the product identified above is in conformity with the set of declared performances. This declaration of performance is issued, in accordance with Regulation (EU) No. 305/2011, under the sole responsibility of the manufacturer identified above
DoP online available at www.svt.de.
Signed for and on behalf of the manufacturer by:

i.V. Christian Meyer-Korte
Head of Product Management

i.V. Andree Schober
Head of chemical department